



698-3800MHz Triplexer (698-960/1710-2170/3300-3800)

JIETONG DIGITAL

GET CONNECTED

Telecommunication Technology & Engineering Accessories

Rev.V1.0

698-3800MHz Triplexer (698-960/1710-2170/3300-3800)

PRODUCT CODE	CMB3-0796.1721.3338-4F155S		
Electrical Specifications			
Frequency	698-960 MHz	1710-2170 MHz	3300-3800 MHz
Insertion Loss	≤ 0.4 dB	≤ 0.4 dB	≤ 0.4 dB
Isolation	≥ 50 dB		
Intermodulation	≤ -155 dBc @ 2 x 43dBm		
VSWR	≤ 1.25		
Impedance	50 Ω		
Power Capacity	≥ 300 W / port		
DC Bypass/Current	Support (≤3 A), Customizable for each port		
Environment Specifications			
Lighting Protection	8/20 us,20KA; 10/350 us pulse, 3KA		
Safety	EN 60 950		
Environment	ETS 300 019		
Operating Temperature	-35 °C to +65 °C		
Storage Temperature	-40 °C to +85 °C		
Relative humidity	0-95%		
Application	IP67 (Indoor and Outdoor)		
Mechanical Specifications			
Dimensions	170 x 145 x 50 mm		
Weight	≤ 2.60 Kg		
RF Connector	4.3-10 female		
Mounting Type	Wall or Pole		
Installation Brackets	IK-CBAL300, 1 pair (Inclusive)		

Outline Drawing

