



698-3800MHz Hexaplexer (698-806/824-960/1710-1880/1920-2170/2500-2700/3500-3800)

PRODUCT CODE	CMB6-0708/0809.1718.1922.2327.3338-4F155S					
Electrical Specifications						
Frequency (MHz)	698-806	824-960	1710-1880	1920-2170	2500-2690	3500-3800
Insertion Loss (dB)	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5	≤ 0.5
Isolation (dB)	≥ 50 dB					
Intermodulation	≤ -155 dBc @ 2 x 43 dBm					
VSWR	≤ 1.3					
Impedance	50 Ω					
Power Capacity	≤ 300 W / port					
Environment Specifications						
Lighting Protection	3kA; 10/350 μs pulse					
Safety	EN 60 950					
Environment	ETS 300 019					
Operating Temperature	-35 °C to +65 °C					
Storage Temperature	-40 °C to +85 °C					
Relative humidity	0-95%					
Application	IP67 (Indoor or Outdoor)					
Mechanical Specifications						
Dimensions	330 x 170 x 62 mm					
Weight	≤ 4.0 Kg					
RF Connector	4.3-10 female					
Mounting Type	Wall or Pole					
Installation Brackets	IK-CBAL300, 1 pair (Inclusive)					

Outline Drawing

