

## Indoor Mobile Signal Jammer

**Model: TSJ5-25-68**

The Mobile Signal Jammer can help to block the mobile signals for any area that are confronted with cellular communication problems: for example, loud incoming call rings, loud telephone conversations, secret leaking and bomb explosion through Mobiles, electromagnetic radiation to gas station, chemical material warehouse and hospital equipments. This product is suitable in executive offices, board meetings, conferences, seminars, libraries, cinemas, religious places, public transport, concert halls, restaurants and educational institutions, Prisons, etc.

Mobile Signal Jammer transmits strong power radio signals to cut-off communications between Mobile and cellular base-stations, effectively disabling mobile phones within the shielding range of the jammer, preventing them from receiving signals and from transmitting signals.

Upon activating Mobile Signal Jammer, all idle phones will indicate “ NO SERVICE” . Incoming calls are blocked as if the cellular phone is OFF. When Mobile Signal Jammer is turned off, all cellular phones will automatically re-establish communications and provide full service.



### Features

- Special technology to prevent interference between each frequency band;
- Only interfere downlink frequency of mobile system, without disturb normally working of Base Stations
- Broadband segment covering, Can jam all wireless signals: 2G, 3G, 4G, WiFi, Bluetooth and GPS.
- Each frequency band controlled by independent RF ON/OFF switches
- High performance heat sink, to ensure long-term use of the equipment.
- Easy operation and installation

### Applications

It is used for prisons, highway gates, main road, stations, harbors, airports, scenic spots, exhibition centers, basements, shopping malls, ...

## Technical Specifications

Items	Specifications				
<b>Jamming Systems</b>	Broadband Segment Covering, Can Jam All Wireless Signals: 2G, 3G, 4G, Bluetooth, WiFi, GPS(One Casing Supports up to Six Frequency Bands)				
<b>Output Port</b>	LTE700				
	UMTS/LTE900				
	DCS/LTE 1800				
	UMTS/LTE2100				
	LTE2600				
<b>Jamming Frequencies</b>	758~803MHz				
	935~960MHz				
	1805~1880MHz				
	2110~2170MHz				
	2620~2690MHz				
<b>Output Power</b>	700MHz	900MHz	1800MHz	2100MHz	2600MHz
	37dBm/5W	37dBm/5W	37dBm/5W	37dBm/5W	37dBm/5W
<b>Total RF Output Power</b>	25W				
<b>Connector Type</b>	SMA-Female				
<b>Power Supply</b>	AC110/220V				
<b>Power Consumption</b>	≤ 80W				
<b>Dimensions</b>	318×265×113 mm				
<b>Weight</b>	≤ 10kg				
<b>Application</b>	Indoor(IP30)				
<b>Temperature Range</b>	-20 to +55°C				
<b>Accessories</b>	5Pcs Antennas				
<b>Local Control</b>	Web Browser GUI Local Via RJ-45 Interface				
<b>Remote Control &amp; Monitor</b>	IP Connectivity. Output Power, Temperature, VSWR and Door Guarding and Modules' Working Status Can Be Monitored				