

Feeder Cable

LHF Series

Low Loss Flexible Foam Dielectric Feeder



1/2"
LHF 12D / LHF-FR 12D



7/8"
LHF 22D / LHF-FR 22D



1-1/4"
LHF 33D / LHF-FR 33D



1-5/8"
LHF 42D / LHF-FR 42D

Construction

		LHF 12D (1/2")	LHF 22D (7/8")	LHF 33D (1-1/4")	LHF 42D (1-5/8")
Inner Conductor	Material / Construction	Copper-Clad Aluminum Wire	Smooth Copper Tube	Smooth Copper Tube	Helically Corrugated Copper Tube
	Diameter (mm)	5.0	9.4	13.7	18.1
Dielectric	Material / Construction	Foamed Polyethylene	Foamed Polyethylene	Foamed Polyethylene	Foamed Polyethylene
	Diameter (mm)	12.5	23.0	33.6	43.5
Outer Conductor	Material / Construction	Annularly Corrugated Copper Tube	Annularly Corrugated Copper Tube	Annularly Corrugated Copper Tube	Annularly Corrugated Copper Tube
	Diameter (mm)	14.2	25.2	36.4	46.5
Jacket Diameter	Standard Jacket (mm)	16.4	28.2	39.4	50.0
	Halogen-Free / Flame-Retardant Jacket (mm)	16.4	28.2	39.4	50.0

Mechanical Characteristics

		LHF 12D (1/2")	LHF 22D (7/8")	LHF 33D (1-1/4")	LHF 42D (1-5/8")
Min. Bending Radius (mm)		125	250	380	500
Recommended Operating Temperature	Standard Jacket (°C)	-40 ~ +80	-40 ~ +80	-40 ~ +80	-40 ~ +80
	Halogen-Free / Flame-Retardant Jacket (°C)	-30 ~ +80	-30 ~ +80	-30 ~ +80	-30 ~ +80
Nominal Weight	Standard Jacket (kg/m)	0.23	0.46	0.84	1.09
	Halogen-Free / Flame-Retardant Jacket (kg/m)	0.25	0.51	0.91	1.19
Flat Plate Crush Resistance (kg/mm)		2.0	1.4	2.4	1.6
Max. Pulling Force (kg)		113	147	260	181

Electrical Characteristics

		LHF12D (1/2")	LHF22D (7/8")	LHF33D (1-1/4")	LHF42D (1-5/8")
DC Resistance Q/1,000m (Q/1,000ft)	Inner Conductor	1.6 (0.5)	1.5 (0.5)	1.1 (0.3)	1.4 (0.4)
	Outer Conductor	1.9 (0.6)	1.9 (0.6)	1.0 (0.3)	0.6 (0.2)
Insulation Resistance (MΩ · km)		10,000	10,000	10,000	10,000
Dielectric Strength (for 1 Min.)		DC 4,000V	DC 6,000V	DC 10,000V	DC 11,000V
Velocity of Propagation (%)		89	89	89	89
Peak Power Rating (kW)		40	91	200	302
Max. Operating Frequency (GHz)		8.8	4.9	3.3	2.5
Characteristic Impedance (Ω)		50	50	50	50
Return Loss (Typical Value) (dB)		28	28	28	28

Attenuation(at 20°C) & Average Power Rating(at Ambient 40°C, Inner Conductor 100°C)

Frequency(MHz)		LHF 12D (1/2")	LHF 22D (7/8")	LHF 33D (1-1/4")	LHF 42D (1-5/8")
Attenuation dB/100m (dB/100ft)	30	1.14 (0.35)	0.59 (0.18)	0.42 (0.13)	0.33 (0.10)
	100	2.12 (0.65)	1.13 (0.34)	0.79 (0.24)	0.64 (0.20)
	150	2.60 (0.79)	1.40 (0.43)	0.98 (0.30)	0.80 (0.24)
	450	4.58 (1.40)	2.52 (0.77)	1.78 (0.54)	1.48 (0.45)
	824	6.31 (1.92)	3.51 (1.07)	2.51 (0.77)	2.11 (0.64)
	894	6.55 (2.00)	3.67 (1.12)	2.64 (0.81)	2.20 (0.67)
	960	6.84 (2.08)	3.82 (1.16)	2.75 (0.84)	2.31 (0.70)
	1,000	7.00 (2.13)	3.92 (1.19)	2.79 (0.85)	2.38 (0.73)
	1,700	9.32 (2.84)	5.29 (1.61)	3.84 (1.17)	3.28 (1.00)
	1,800	9.61 (2.93)	5.47 (1.67)	3.97 (1.21)	3.40 (1.04)
	2,000	10.19 (3.11)	5.81 (1.77)	4.25 (1.30)	3.63 (1.11)
	2,400	11.10 (3.38)	6.46 (1.97)	4.73 (1.44)	4.05 (1.23)
	2,700	12.53 (3.73)	6.88 (2.10)	5.11 (1.56)	4.18 (1.27)
	3,000	12.96 (3.95)	7.37 (2.25)	5.43 (1.66)	-
	3,500	13.92 (4.24)	8.08 (2.46)	-	-
	4,000	15.27 (4.65)	8.75 (2.67)	-	-
5,000	17.15 (5.23)	9.99 (3.04)	-	-	
Average Power Rating (kW)	30	6.10	13.58	21.30	30.60
	100	3.32	7.36	11.50	16.42
	150	2.71	5.98	9.32	13.28
	450	1.55	3.38	5.23	7.37
	824	1.13	2.46	3.78	5.28
	894	1.09	2.36	3.61	5.05
	960	1.05	2.27	3.48	4.85
	1,000	1.03	2.22	3.40	4.74
	1,700	0.78	1.67	2.53	3.50
	1,800	0.76	1.62	2.45	3.39
	2,000	0.71	1.53	2.31	3.18
	2,400	0.65	1.38	2.09	2.86
	2,700	0.61	1.31	1.95	2.77
	3,000	0.58	1.22	1.84	-
	3,500	0.53	1.12	-	-
	4,000	0.50	1.04	-	-
5,000	0.44	0.92	-	-	

* Attenuation is typical value

* Standard Conditions : V.S.W.R 1.0 ; Ambient Temperature 20°C

* Specifications Subject to change without notice