

## N Series RF Coaxial Attenuator



Item Name:	Fixed Attenuator	V.S.W.R:	$\leq 1.20$
Model:	ATF-2W-3GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	$\pm 0.5\text{dB}$
Impedance:	50 $\Omega$	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Brass
Power:	2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	$\leq 1.20$
Model:	ATF-5W-3GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	$\pm 0.5\text{dB}$
Impedance:	50 $\Omega$	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	$\leq 1.15$
Model:	ATF-5W-4GNXXR/B	Attenuation:	3 ~ 30 dB
Frequency:	DC-4000MHz	Accuracy:	$\pm 0.5\text{dB}$
Impedance:	50 $\Omega$	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use









Item Name:	Fixed Attenuator	V.S.W.R:	$\leq 1.20$
Model:	ATF-5W-4GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-4000MHz	Accuracy:	$\pm 0.5\text{dB}$
Impedance:	50 $\Omega$	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	$\leq 1.20$
Model:	ATF-10W-3GNEXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	$\pm 0.5\text{dB}$
Impedance:	50 $\Omega$	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	10 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	$\leq 1.20$
Model:	ATF-10W-3GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	$\pm 0.5\text{dB}$
Impedance:	50 $\Omega$	Temperature:	-35°C- +85°C

	Connector: N Male-N Female	Radiator: Aluminium
	Power: 10 W (Average)	Annotation: Indoor Use
	Item Name: Fixed Attenuator	V.S.W.R: $\leq 1.20$
	Model: ATF-10W-4GNXXR	Attenuation: 3 ~ 30 dB
	Frequency: DC-4000MHz	Accuracy: $\pm 0.5\text{dB}$
	Impedance: 50 $\Omega$	Temperature: -35°C- +85°C
	Connector: N Male-N Female	Radiator: Aluminium
	Power: 10 W (Average)	Annotation: Indoor Use
	Item Name: Fixed Attenuator	V.S.W.R: $\leq 1.35$
	Model: ATF-10W-18GNXXR	Attenuation: 3 ~ 30 dB
	Frequency: DC-18000MHz	Accuracy: $\pm 0.5\text{dB}$
	Impedance: 50 $\Omega$	Temperature: -35°C- +85°C
	Connector: N Male-N Female	Radiator: Aluminium
	Power: 10 W (Average)	Annotation: Indoor Use
	Item Name: Fixed Attenuator	V.S.W.R: $\leq 1.20$
	Model: ATF-20W-3GNXXR	Attenuation: 3 ~ 30 dB
	Frequency: DC-3000MHz	Accuracy: $\pm 0.5\text{dB}$
	Impedance: 50 $\Omega$	Temperature: -35°C- +85°C
	Connector: N Male-N Female	Radiator: Aluminium
	Power: 20 W (Average)	Annotation: Indoor Use
	Item Name: Fixed Attenuator	V.S.W.R: $\leq 1.20$
	Model: ATF-20W-4GNXXR	Attenuation: 3 ~ 30 dB
	Frequency: DC-4000MHz	Accuracy: $\pm 0.5\text{dB}$
	Impedance: 50 $\Omega$	Temperature: -35°C- +85°C
	Connector: N Male-N Female	Radiator: Aluminium
	Power: 20 W (Average)	Annotation: Indoor Use
	Item Name: Fixed Attenuator	V.S.W.R: $\leq 1.20$
	Model: ATF-25W-3GNEXX	Attenuation: 3 ~ 30 dB
	Frequency: DC-3000MHz (DC-4000MHz)	Accuracy: $\pm 0.5\text{dB}$
	Impedance: 50 $\Omega$	Temperature: -35°C- +85°C
	Connector: N Male-N Female	Radiator: Aluminium
	Power: 25 W (Average)	Annotation: Indoor Use
	Item Name: Fixed Attenuator	V.S.W.R: $\leq 1.20$
	Model: ATF-25W-3GNXXR	Attenuation: 3 ~ 30 dB
	Frequency: DC-3000MHz	Accuracy: $\pm 0.5\text{dB} / \pm 1.0\text{dB}$

Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	25 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-25W-4GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-4000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	25 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-25W-3GNXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	25 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-30W-3GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	30 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-30W-4GNXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-4000MHz	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	30 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-30W-3GNXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium

	Power: 30 W (Average) Item Name: Fixed Attenuator Model: ATF-50W-3GNXXR Frequency: DC-3000MHz Impedance: 50 Ω Connector: N Male-N Female Power: 50 W (Average)	Annotation: Indoor Use V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 40 dB Accuracy: ±0.5dB / ±1.0dB Temperature: -35°C- +85°C Radiator: Aluminium Annotation: Indoor Use
	Item Name: Fixed Attenuator Model: ATF-50W-4GNXXR Frequency: DC-4000MHz Impedance: 50 Ω Connector: N Male-N Female Power: 50 W (Average)	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 40 dB Accuracy: ±0.5dB / ±1.0dB Temperature: -35°C- +85°C Radiator: Aluminium Annotation: Indoor Use
	Item Name: Fixed Attenuator Model: ATF-50W-3GNEXX Frequency: DC-3000MHz (DC-4000MHz) Impedance: 50 Ω Connector: N Male-N Female Power: 50 W (Average)	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 40 dB Accuracy: ±0.5dB / ±1.0dB Temperature: -35°C- +85°C Radiator: Aluminium Annotation: Indoor Use
	Item Name: Fixed Attenuator Model: ATF-50W-3GNXX Frequency: DC-3000MHz (DC-4000MHz) Impedance: 50 Ω Connector: N Male-N Female Power: 50 W (Stop Production)	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 40 dB Accuracy: ±0.5dB / ±1.0dB Temperature: -35°C- +85°C Radiator: Aluminium Annotation: Indoor Use
	Item Name: Fixed Attenuator Model: ATF-100W-6GNXXR Frequency: DC-6000MHz Impedance: 50 Ω Connector: N Male-N Female Power: 100 W	V.S.W.R: ≤ 1.25 Attenuation: 3 ~ 40 dB Accuracy: ±0.5dB / ±1.0dB Temperature: -35°C- +85°C Radiator: Aluminium Annotation: Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-100W-3GNXX	Attenuation:	3 ~ 40 dB
Frequency:	DC-3000MHz	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	100 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-300W-3GNXX	Attenuation:	3~ 50 dB
Frequency:	DC-3000MHz	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	N Male-N Female	Radiator:	Aluminium
Power:	300 W (Average)	Annotation:	Indoor Use

### 7/16(DIN) Series RF Coaxial Attenuator



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-2W-3GDCXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-5W-3GDEXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-5W-3GDSXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	5 W (Stop Production)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator(Round)	V.S.W.R:	≤ 1.20
Model:	ATF-10W-3GDEXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB

Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	10 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator(Round)	V.S.W.R:	≤ 1.20
Model:	ATF-10W-3GDXXR	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	10 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator(Round)	V.S.W.R:	≤ 1.20
Model:	ATF-25W-3GDXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	25 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-50W-3GDXX	Attenuation:	3 ~ 40 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	50 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-100W-3GDXX	Attenuation:	3 ~ 40 dB
Frequency:	DC-3000MHz	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Female-DIN Female	Radiator:	Aluminium
Power:	100 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-100W-3GDBXX	Attenuation:	3 ~ 40 dB
Frequency:	DC-3000MHz	Accuracy:	±0.5dB / ±1.0dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	DIN Male-DIN Female	Radiator:	Aluminium
Power:	100 W (Average)	Annotation:	Indoor Use

### 4.3/10 DIN Series RF Coaxial Attenuator



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-2W-3G43MDXXR	Attenuation:	3 ~ 40 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	4.3-10 MD/M-4.3-10MD/F	Radiator:	Aluminium
Power:	2 W (Average)	Annotation:	Indoor Use

### SMA Series RF Coaxial Attenuator



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-1W(2W)-3GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Brass
Power:	1/2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-1W(2W)-6GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-6000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Brass
Power:	1/2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-1W(2W)-18GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-18000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Brass
Power:	1/2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-2W-6GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-6000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Brass
Power:	2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.30
Model:	ATF-2W-18GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-18000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Brass
Power:	2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.35
Model:	ATF-2W-26.5GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-26500MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Brass
Power:	2 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	ATF-5W-3GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz (DC-4000MHz)	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.25
Model:	ATF-5W-6GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-6000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use



Item Name:	Fixed Attenuator	V.S.W.R:	≤ 1.30
Model:	ATF-5W-18GSMXX	Attenuation:	3 ~ 30 dB
Frequency:	DC-18000MHz	Accuracy:	±0.5dB
Impedance:	50 Ω	Temperature:	-35°C- +85°C
Connector:	SMA Male-SMA Female	Radiator:	Aluminium
Power:	5 W (Average)	Annotation:	Indoor Use

### Low PIM RF Coaxial Attenuator



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	LPATD-5W-3GNXX *	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.8~1.0dB
Impedance:	50 Ω	Weight:	0.25kg
PIM:	-140dBc@20W(Direct connect)	Radiator:	Aluminium



Power:	5W	Temperature	-25°C- +75°C
Connector:	N/Male -Female	Annotation:	Indoor Use



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	LPATD-10W-3GNXX *	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.8~1.0dB
Impedance:	50 Ω	Weight:	0.25kg
PIM:	-140dBc@20W(Direct connect)	Radiator:	Aluminium
Power:	10W	Temperature	-25°C- +75°C
Connector:	N/Male -Female	Annotation:	Indoor Use



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	LPATD-20W-3GNXX *	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.8~1.0dB
Impedance:	50 Ω	Weight:	0.25kg
PIM:	-140dBc@20W(Direct connect)	Radiator:	Aluminium
Power:	20W	Temperature	-25°C- +75°C
Connector:	N/Male -Female	Annotation:	Indoor Use



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	LPATD-25W-3GNXX *	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.8~1.0dB
Impedance:	50 Ω	Weight:	0.25kg
PIM:	-140dBc@20W(Direct connect)	Radiator:	Aluminium
Power:	25W	Temperature	-25°C- +75°C
Connector:	N/Male -Female	Annotation:	Indoor Use



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	LPATD-25W-3G41MDXX *	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.8~1.0dB
Impedance:	50 Ω	Weight:	0.25kg
PIM:	-140dBc@20W(Direct connect)	Radiator:	Aluminium
Power:	25W	Temperature	-25°C- +75°C
Connector:	4.1/9.5 MINI DIN Male/Female	Annotation:	Indoor Use



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	≤ 1.20
Model:	LPATD-25W-3G43MDXX *	Attenuation:	3 ~ 30 dB
Frequency:	DC-3000MHz	Accuracy:	±0.8~1.0dB
Impedance:	50 Ω	Weight:	0.25kg
PIM:	-140dBc@20W(Direct connect)	Radiator:	Aluminium
Power:	25W	Temperature	-25°C- +75°C

	Connector: 4.3/10 MINI DIN Male/Female	Annotation: Indoor Use
	Item Name: Low PIM Fixed Attenuator Model: LPATF-50W-727-NXX ** Frequency: 698-2700MHz Impedance: 50 Ω PIM: -160dBc@20W(Reflection) *** Power: 50W Connector: N/Male-Female	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 30 dB Accuracy: ±0.8~1.0dB Weight: 3.1kg Radiator: Aluminium Temperature: -35°C- +75°C Annotation: Indoor Use
	Item Name: Low PIM Fixed Attenuator Model: LPATF-50W-727-DXX ** Frequency: 698-2700MHz Impedance: 50 Ω PIM: -160dBc@20W(Reflection) *** Power: 50W Connector: 7/16(DIN)/Male-Female	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 30 dB Accuracy: ±0.8~1.0dB Weight: 3.1kg Radiator: Aluminium Temperature: -35°C- +75°C Annotation: Indoor Use
	Item Name: Low PIM Fixed Attenuator Model: LPATF-100W-727-NXX ** Frequency: 698-2700MHz Impedance: 50 Ω PIM: -160dBc@20W(Reflection) *** Power: 100W Connector: N/Male-Female	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 30 dB Accuracy: ±0.8~1.0dB Weight: 3.1kg Radiator: Aluminium Temperature: -35°C- +75°C Annotation: Indoor Use
	Item Name: Low PIM Fixed Attenuator Model: LPATF-100W-727-DXX ** Frequency: 698-2700MHz Impedance: 50 Ω PIM: -160dBc@20W(Reflection) *** Power: 100W Connector: 7/16(DIN)/Male-Female	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 30 dB Accuracy: ±0.8~1.0dB Weight: 3.1kg Radiator: Aluminium Temperature: -35°C- +75°C Annotation: Indoor Use
	Item Name: Low PIM Fixed Attenuator Model: LPATF-100W-727-41MDXX ** Frequency: 698-2700MHz Impedance: 50 Ω PIM: -160dBc@20W(Reflection) *** Power: 100W Connector: 4.1/9.5 DIN Male-Female	V.S.W.R: ≤ 1.20 Attenuation: 3 ~ 30 dB Accuracy: ±0.8~1.0dB Weight: 3.1kg Radiator: Aluminium Temperature: -35°C- +75°C Annotation: Indoor Use



Item Name:	Low PIM Fixed Attenuator	V.S.W.R:	$\leq 1.20$
Model:	LPATF-100W-727-43MDXX **	Attenuation:	3 ~ 30 dB
Frequency:	698-2700MHz	Accuracy:	$\pm 0.8 \sim 1.0$ dB
Impedance:	50 $\Omega$	Weight:	3.1kg
PIM:	-160dBc@20W(Reflection) ***	Radiator:	Aluminium
Power:	100W	Temperature	-35°C- +75°C
Connector:	4.3/10 DIN/Male-Female	Annotation:	Indoor Use

---

\* For this type, the PIM value is direct connection.

\*\* For this type, the PIM value is reflection.

\*\*\* For typical intermodulation , PIM  $\leq -165$ dBc@2X43dBm

---