



Item Name: SC/PC-ST/PC Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: FC/PC-ST/PC Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: D4 Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: FC/PC-SC/PC Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: DIN Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: SMA/MM Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: FC/PC(Separate) Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal/Plastic

Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: FC/PC(Integrative) Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal/Plastic
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: SC/PC/SM Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: SC/PC/MM Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Plastic
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles




Item Name: SC/APC Adapter Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Plastic
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: SC/APC (Double) Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Plastic
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name: SC/PC (Double) Repeatability: $\leq 0.2\text{dB}$
Wavelength: 1200~1600nm Material: Metal
Insertion Loss: $\leq 0.3\text{dB}$ Temperature: $-40^{\circ}\text{C}\sim 75^{\circ}\text{C}$
Exchangeability: $\leq 0.2\text{dB}$ Durability: 500 Cycles



Item Name:	FC/PC (Double)	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	LC/PC/SM Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	LC/PC/MM Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	LC/APC Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	LC/PC/SM Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	LC/PC/SM Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles

Item Name:	LC/APC Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Plastic
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	MTRJ Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Metal
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	MPO Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Metal
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	E2000 Adapter	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Metal
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	Fast Connector	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Metal
Insertion Loss:	≤0.3dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles



Item Name:	Fast Connector	Repeatability:	≤0.2dB
Wavelength:	1200~1600nm	Material:	Metal
Insertion Loss:	≤0.5dB	Temperature:	-40°C~75°C
Exchangeability:	≤0.2dB	Durability:	500 Cycles
