

TSLA37A-1



TSLA37A-1



700+900+2100 MHz Triple Wide Band RF Repeater(37dBm)

??- ????
On Order
 ★★★★★

[??????????](#)

??				
System		LTE700	LTE900	UMTS/LTE2100
Frequency Range	Uplink	703~748MHz	885~915MHz	1920~1980MHz
	Downlink	758~803MHz	930~960MHz	2110~2170MHz
Bandwidth		45MHz	30MHz	60MHz
Output Power	Uplink	30±2dBm	30±2dBm	30±2dBm
	Downlink	33±2dBm	33±2dBm	37±2dBm
Maximum Gain		85±3dB		
Gain Adjustment Range		0~31dB @ Step of 1dB		
VSWR		? 1.5		
Maximum Input Power(Non-Destructive)		0dBm		
Spurious Emission		9KHz~1GHz: ? -36dBm		
		1GHz~12.75GHz: ? -30dBm		
Noise Figure		? 6dB		
System Delay		? 1.5?s		
I/O Impedance		50?		
RF Connector		2XN-Female		
Power Supply		AC:100-240V, 50/60Hz		
Dimensions		500*440*235mm		

Weight	?45kg
Operating Temperature	-25 ~ +55 °C
Application	Indoor or Outdoor(IP65)
Relative Humidity Range	? 95%(Non Condensing)
Local Control	Web Browser GUI Local Via RJ-45 Interface or WiFi Hotspot
Remote Mode	Wireless Modem(3G/4G), IP Connectivity
NMS Function	Real-time Alarm for Door Status, Temperature, Power Supply,VSWR,etc; Remote Control such as Turn On/Off, Increasing/Decreasing Output Power, etc; Real-time Status for UL/DL Gain, Input/Output Power, All Status of Repeater etc;