

TS50A37B1



3300-3570 MHz 5GNR Single Band RF Repeater (37dBm)

??: ????
On Order
★★★★★

[????????](#)

??

- Ø ???????????
- Ø IP65??????????????????
- Ø ?????????????????????????????????????
- Ø ???????????
- Ø ??5G??TDD????????5G????????????
- Ø ???????ALC????????????
- Ø ?????????????
- Ø ?????????????????????
- Ø USB ????????????????? IP ? NMS????????????????????????????????
- Ø Two signal ports with full duplex design.
- Ø Aluminum-alloy casing with IP65 protection has high resistance to dust, water and corrosion.
- Ø Low interference to BTS by adopting linear amplifier with high gain and low noise
- Ø Linear power amplification to effectively suppress inter-modulation and spurious emission.
- Ø Stable and improved signal transmission quality.
- Ø Built-in 5G Dynamic TDD Sync Detection Module, automatic completion of 5G wireless network cell search and wireless signaling processing.
- Ø Smart Automatic Level Control (ALC) ensures output level stable and adjustable continuously.
- Ø Auto Isolation check between service and donor antennas.
- Ø Smart mode to auto-adjust gain according to the isolation and signal level received by donor site.

- Ø USB port provides a link to a notebook for local supervision or IP Based NMS (Network Management System) that can remotely supervise Repeater's working status and download operational parameters to the Repeater Via Ethernet or LAN