

JTD-GOF208R+GOF208L

JTD-GOF208R+GOF208L



1557.5-1587.5 MHz GPS Over Fiber

?: ???
1-4 Weeks
★ ★ ★ ★

[????????](#)

??

2 ??????????????????????

2

??? 30dB?????

2 ??????????????

2 ??????1?????????8???

2 ??????1?????

2 (????????????????(RJ45????)

2 (????????????????(RJ45????)

2 ?????????

2 ?????8?(12/16?????)

2 ???GPS/Beidu2 81????

2 ?48V DC?????

2 ??????????

2 ??LNA??????

2 ??????????

- 2 Dual loop antenna, automatic and manual switching function (remote host);
- 2 Gain: 30dB fixed gain;
- 2 Antenna output port status monitoring and alarm;
- 2 The remote host is equipped with 1 optical port as standard (up to 8 additional ports);
- 2 The local host is equipped with 1 optical receiving port as standard;
- 2 (Near-end host) Two-way dry contact alarm function (RJ45 interface);
- 2 (Remote host) Four-way dry contact alarm function (RJ45 interface);
- 2 Buzzer alarm function;
- 2 The output port is equipped with 8 ports as standard (12/16 ports are optional);
- 2 Real-time display of GPS/Beidu2 81 information;
- 2 Dual 48V DC power supply support;
- 2 Software management, network management monitoring;
- 2 Support LNA backup and detection;
- 2 Long-distance optical fiber transmission of signal;