

## JTD-GLNA-1164-1616-30-DV4



JTD-GLNA-1164-1616-30-DV4



??GPS????(4?)(Rack-mounted GPS digital display adjustable amplifier (4 out))

?: ????  
1-2 months  
★ ★ ★ ★ ★

[????????](#)

??

## **JTD-GLNA-1164-1616-30-DV4** ??????????19????????????????????????????????

2 ??????:LED????????????????????

2 ?????????????????????????????

2 ?????????????????????????;

2 RS-232 ????????

2 ????????

2 ???????

?????AC 110~220V/ DC 12 V,?????1W

?????GPS, Galileo,  
GLONASS?Beidou2?????????0-30dB,?????3dB.?????100mA,????????????

**JTD-GLNA-1164-1616-30-DV4** is our company's latest 19-inch rack-mounted single-stage low-noise amplifier. Its features are as follows:

- 2 Digital display gain: LED digital display, clearly showing the current amplifier gain;
- 2 Button-type gain adjustment: You can adjust the gain you need by pressing the up and down buttons;
- 2 Power control: Toggle the power switch to easily control the power supply status of the system;

<sup>2</sup> RS-232 sequence command control;

<sup>2</sup> Input port power-on setting;

<sup>2</sup> Four output ports.

### Wide Voltage Input AC 110~220V/ DC 12 V, Power Consumption less than 1W

Covered frequencies include GPS, Galileo, GLONASS and Beidou2 frequency bands. Its gain is 0-30dB, the noise coefficient is less than 3dB. The power consumption is less than 100mA, and the equipment and receiving antenna are installed vertically.