

JTD-GLNA-1164-1616-30-DV8



JTD-GLNA-1164-1616-30-DV8



??GPS????(8?)(Rack-mounted GPS digital display adjustable amplifier (8 out))

?: ???
1-2 months
★ ★ ★ ★ ★

[????????](#)

??

JTD-GLNA-1164-1616-30-DV8????????19????????????????????

- 2 ?????:LED????????????????
- 2 ?????????????????????????
- 2 ?????????????????????;
- 2 RS-232 ????????
- 2 ?????????
- 2 ???????

????AC 110~220V/ DC 12 V,????1W

????GPS, Galileo,
GLONASS?Beidou????????0-30dB,????3dB.????100mA,????????

JTD-GLNA-1164-1616-30-DV8 is our company's latest 19-inch rack-mounted single-stage low-noise amplifier. Its features are as follows:

- 2 Digital display gain: LED digital display, clearly showing the current amplifier gain;
- 2 Button-type gain adjustment: You can adjust the gain you need by pressing the up and down buttons;
- 2 Power control: Toggle the power switch to easily control the power supply status of the system;

² RS-232 sequence command control;

² Input port power-on setting;

² Eight output ports.

Wide Voltage Input AC 110~220V/ DC 12 V, Power Consumption less than 1W

Covered frequencies include GPS, Galileo, GLONASS and Beidou2 frequency bands. Its gain is 0-30dB, the noise coefficient is less than 3dB. The power consumption is less than 100mA, and the equipment and receiving antenna are installed vertically.