

JTD-GLNA-1164-1616-30-DV



JTD-GLNA-1164-1616-55-DV



GPS?????????(GPS digital display adjustable amplifier)

?: ????
1-2 months

[?????????](#)

??

JTD-GLNA-1164-1616-30-DV4????????????????????????????????????

- 2 ??????:LED????????????????????
- 2 ?????????????????????????????
- 2 ?????????????????????????;
- 2 RS-232 ????????
- 2 ????????????
- 2 ????????

?????GPS, Galileo,
GLONASS?Beidou2????????????0-30dB,?????3dB.????100mA,????????????

JTD-GLNA-1164-1616-30-DV is the latest single-stage low-noise amplifier launched by our company. It has several characteristics as follows:

² Digital display gain: LED digital display clearly shows the gain of the current amplifier;

² Push-button gain adjustment: You can adjust the gain you need by pressing the up and down buttons;

² Power control: Toggle the power switch to easily control the power supply status of the system;

² RS-232 serial command control;

² Power-on setting of input and output terminals;

² Single output port.

Covered frequencies include GPS, Galileo, GLONASS and Beidou2 frequency bands. Its gain is 0-30dB, and the noise coefficient is less than 3dB. The power consumption is less than 100mA, and the equipment and receiving antenna are installed vertical