

JTD-RP-DWN-20-40



LTE1800+LTE2100+5GNR (TDD-3500) Pico RF Repeater (20dBm)

??: ????
On Order
★★★★★

[????????](#)

??

- ????????????
- Ø ?????????????????????
- Ø ?????????
- Ø ??5G??TDD?????????5G????????????
- Ø ???????ALC????????????
- Ø ?????????????
- Ø ?????????????????
- Ø USB?????????????IP?NMS????????????????????????????
- Ø Two signal ports with full duplex design.
- Ø Aluminum-alloy casing with IP65 protection has high resistance to dust, water and corrosion.
- Ø Linear power amplification to effectively suppress inter-modulation and spurious emission.
- Ø Adopting filter with highly selectivity and low insertion loss eliminates interference between uplink and downlink.
- Ø Stable and improved signal transmission quality.
- Ø Built-in 5G Dynamic TDD Sync Detection Module, automatic completion of 5G wireless network cell search and wireless signaling processing.
- Ø Smart Automatic Level Control (ALC) ensures output level stable and adjustable continuously.
- Ø Auto Isolation check between service and donor antennas.
- Ø Smart mode to auto-adjust gain according to the isolation and signal level received by donor site.
- Ø USB port provides a link to a notebook for local supervision or IP Based NMS(Network Management System) that can remotely supervise repeater's working status and download operational parameters to the repeater Via Ethernet.