

## JTD-RP-DWN-20-40



JTD-RP-DWN-20-40



LTE1800+LTE2100+5GNR (TDD-3500) Pico RF Repeater (20dBm)

??: ????  
**On Order**  
★★★★★

[??????????](#)

??

????????????????

o ?????????????????????????????????

o ?????????????

o ??5G??TDD??????????5G????????????

o ?????????ALC????????????

o ?????????????????

o ?????????????????????????????

o USB????????????????IP?NMS????????????????????????????????

o Two signal ports with full duplex design.

o Aluminum-alloy casing with IP65 protection has high resistance to dust, water and corrosion.

o Linear power amplification to effectively suppress inter-modulation and spurious emission.

o Adopting filter with highly selectivity and low insertion loss eliminates interference between uplink and downlink.

o Stable and improved signal transmission quality.

o Built-in 5G Dynamic TDD Sync Detection Module, automatic completion of 5G wireless network cell search and wireless signaling processing.

o Smart Automatic Level Control (ALC) ensures output level stable and adjustable continuously.

o Auto Isolation check between service and donor antennas.

o Smart mode to auto-adjust gain according to the isolation and signal level received by donor site.

o USB port provides a link to a notebook for local supervision or IP Based NMS(Network Management System) that can remotely supervise repeater's working status and download operational parameters to the repeater Via Ethernet.