

JTD-LTE-M2-S24



JTD-LTE-M2-S24



FDD-LTE Small cell

?: ????
1-2 months
★ ★ ★ ★ ★

[?????????](#)

??

- Ø ??FDD-LTE?????Band1?Band3??????????????????
- Ø ??20MHz/15MHz/10MHz/5MHz?FDD-LTE????
- Ø ??????GPS???1588v2
- Ø SON????????????????????????????????
- Ø ??IPSec?????IKEv2????????????????????
- Ø ??????????????IP????????????????????
- Ø ??????MIMO 2*2(24dBm)????????????????????
- Ø ??????????TR069????????????
- Ø ???????
- Ø ?????????????????????????????
- Ø ?????????????????????????
- Ø ??PoE??

Ø Provide FDD-LTE coverage, support Band1 and Band3, and other frequency bands can be configured according to user needs

- Ø Support FDD-LTE channel bandwidth of 20MHz/15MHz/10MHz/5MHz
- Ø Support wireless synchronization, GPS synchronization, 1588v2
- Ø SON function, automatic configuration, automatic management, automatic optimization, plug-and-play design
- Ø Support IPSec channel technology and IKEv2 multiple encryption algorithms to ensure network and information security
- Ø Adopting gigabit adaptive network interface and IP return technology, flat structure, strong compatibility
- Ø Low-power equipment, MIMO 2*2(24dBm),small coverage, support automatic power and coverage adjustment, green and healthy
- Ø Support remote management, adopt TR069 protocol, unified network management operation and maintenance
- Ø Indication for equipment abnormal
- Ø Support mobility management functions such as handover and reselection in the system
- Ø Support inter-network collaboration to improve user perception and system capacity.
- Ø Support PoE power supply