

JTD-RP-EGDWN-17-60



JTD-RP-EGDWN-17-60



700-3500 MHz Penta Band RF Repeater (17dBm)

?: ????
1-2 months

[?????????](#)

??

LTE700+LTE900+LTE1800+LTE/UMTS2100+5GNR 3500-TDD

- u ????????????????
- u ??????????????????????
- u ??????????????????
- u ??????????????
- u ??5G??TDD????????????5G?????????????????
- u ??????????ALC?????????????????
- u ??????????????????????
- u ??????????????????????????????????????
- u ???? AC/DC ??????????
- u ??????????????????

LTE700+LTE900+LTE1800+LTE/UMTS2100+5GNR 3500-TDD

- u Two signal ports with full duplex design.

- u Linear power amplification to effectively suppress inter-modulation and spurious emission.
- u Stable and improved signal transmission quality.
- u Compact size with stable performance.
- u Built-in 5G Dynamic TDD Sync Detection Module, automatic completion of 5G wireless network cell search and wireless signaling processing.
- u Smart Automatic Level Control (ALC) ensures output level stable and adjustable continuously.
- u Auto Isolation check between service and donor antennas.
- u Smart mode to auto-adjust gain according to the isolation and signal level received by donor site.
- u Simple installation with external AC/DC adapter.
- u Cost-effective for practical solutions.