

Internal GPS Passive Ceramic antenna



Internal GPS Passive Ceramic antenna

Internal GPS Passive Ceramic antenna(?????)

??: ????
1-4 Weeks
★★★★★

[??????????](#)

??

???? OEM ? ODM

OEM and ODM is acceptable

Item:	1	2	3	4	5
Model No:	JTD-GP336	JTD-GP325	JTD-GP320	JTD-GP31167	JTD-GP318
Product Appearance:					
Frequency(MHz): (with 70°FOGND Plane)	1561.098 1575.42 1602 1167/1226	1561.098 1575.42 1602	1561.098 1575.42 1602 1167/1226	1561.098 1575.42 1602	1561.098 1575.42
Gain(dB):	11.9 15.1	3.0	11.9 15.2	3.5	2.0
VSWR:	+2.0	+2.0	+2.0	+2.0	+2.0
Impedance(Ω):	50	50	50	50	50
Polarization:	RHCP	RHCP	RHCP	RHCP	RHCP
Dimension(mm):	36×36×4 25×25×4	25×25×4(4)	45×45×6 36×36×4	18×18×4 (2)	18×18×4 (SMD)
Operating Temperature(°C):	-40°~+80°	-40°~+80°	-40°~+80°	-40°~+80°	-40°~+80°

Item:	1	2	3	4	5
Model No:	JTD-GP336	JTD-GP325	JTD-GP320	JTD-GP318	JTD-GP315
Product Appearance:					
Frequency(MHz): (with 70°FOGND Plane)	1561.098 1575.42 1602	1561.098 1575.42 1602	1561.098 1575.42	1561.098 1575.42	1561.098 1575.42
Gain(dB):	5.0	4.0	3.0	2.0	1.5
VSWR:	+2.0	+2.0	+2.0	+2.0	+2.0
Impedance(Ω):	50	50	50	50	50
Polarization:	RHCP	RHCP	RHCP	RHCP	RHCP
Dimension(mm):	36×36×6(4)	25×25×4(4/2)	20×20×4(2)	18×18×4 (2)	15×15×4 (2)
Operating Temperature(°C):	-40°~+80°	-40°~+80°	-40°~+80°	-40°~+80°	-40°~+80°