

External Active GPS antenna



External Active GPS antenna

External Active GPS antenna(???????)

?? : ????
1-4 Weeks
★ ★ ★ ★

[??????????](#)

??

****OEM+ODM

OEM and ODM is acceptable

Item:	1	2	3	4	5
Model No:	ITD-DAM1556A4A	ITD-DAM1556A4E0	ITD-DAM1556A2E1	ITD-818X	ITD-84004
Product Appearance:					
Frequency(MHz):	1561.098 1575.42	1561.098 1575.42	1561.098 1575.42 1602	1561.098 1575.42 1602 11768.1207	1561.098 1575.42
Gain(dB):	3.0	3.0	3.0	3.0	3.0
LAN Gain(dB):	28	28	26	30	28
VSWR:	<+2.0	<+2.0	<+2.0	<+2.0	<+2.0
Return Figure:	<-1.5	<-1.5	<-1.5	<-1.5	<-1.5
Impedance(Ω):	50	50	50	50	50
Polarization:	RHCP	RHCP	RHCP	RHCP	RHCP
Connector:	SMA	SMA	SMA	SMA	SMA
Cable Length:	RG-174	RG-174	RG-174	RG-174	RG-174
Dimension(mm):	48*39*15.2	49*37*16	50*50*15.6	Φ65	55*44*16
Operating Temperature(°C):	-40~+80°	-40~+80°	-40~+80°	-40~+80°	-40~+80°

Item:	1	2	3	4	5
Model No:	ITD-Y112	ITD-Y116	ITD-Y125	ITD-1818	ITD-1515
Product Appearance:					
Frequency(MHz):	1575.42	1561.098 1575.42	1561.098 1575.42 1602	1561.098 1575.42	1575.42
Gain(dB):	0	1.0	2.0	2.0	1.0
LAN Gain(dB):	18	18	26	30	30
VSWR:	<+2.0	<+2.0	<+2.0	<+2.0	<+2.0
Return Figure:	<-1.5	<-1.5	<-1.5	<-1.5	<-1.5
Impedance(Ω):	50	50	50	50	50
Polarization:	RHCP	Line	RHCP	RHCP	RHCP
Connector:	IPex	IPex	IPex	IPex	IPex
Cable Length:	1.13	1.13	1.13	1.13	1.13
Dimension(mm):	12*12*6.6	16*6*6.7	25*25*6.4	18*18*6.8	15*15*6.5
Operating Temperature(°C):	-40~+80°	-40~+80°	-40~+80°	-40~+80°	-40~+80°