

S-Band LNB(F)



S-Band LNB(F)







S-Band LNB(F)

??: ????
On Order
★★★★★

[?????????](#)

??

S-Band LNB(F)

		Input Frequency: 2520~2670MHz Output Frequency: 950~1100MHz L.O. Frequency: 3620MHz	
	Input Frequency	Output Frequency	L.O. Frequency
	2.3 to 2.7GHz	950 to 1350 MHz	3650MHz
	2.2 to 2.7Ghz	1050 to 1550 MHz	3750MHz
	2.5 to 2.9GHz	950 to 1350 MHz	3850MHz
	Special		
	3 to 4 GHz	950 to 1950 MHz	4950MHz
	4 to 5 GHz	750 to 1750 MHz	5750MHz
	5 to 6 GHz	1050 to 2050 MHz	3950MHz
	6 to 7 GHz	950 to 2050 MHz	4505MHz

More Details

L.O. Stability	±1.5MHz(-40°C to +70°C)	Image Rejection	45 dB
Noise Figure	0.4dB	Phase Noise	-95dBc/Hz@100kHz(max), 75dBc/Hz@10kHz(max)
Conversion Gain	55dB	Supply Voltage	12V-24V
Input VSWR	2.0:1	Operating Temperature	-40°C to +70°C
Output VSWR	2.0:1	Storage Temperature	-40°C to +80°C
Output Connector	F-female Connector	Relative Humidity	0%-95%
Output Impedance	75 Ω		