


HFC 12D Series



HFC 12D Series

??-????
 7 Days
 ★★☆☆☆

[??????????](#)

??

Attenuation(at 20 °C) & Average Power Rating(at Ambient 40°C, Inner Conductor 100°C)

Frequency(MHz)	HFC 12D (1/2")	HFC 22D (7/8")	HFC 33D (1-1/4")	HFC 42D (1-5/8")
30	1.17 (0.36)	0.64 (0.20)	0.44 (0.13)	0.36 (0.11)
100	2.17 (0.66)	1.19 (0.36)	0.83 (0.25)	0.67 (0.20)
150	2.67 (0.81)	1.47 (0.45)	1.03 (0.31)	0.84 (0.26)
450	4.75 (1.45)	2.65 (0.81)	1.86 (0.57)	1.53 (0.47)
824	6.49 (1.98)	3.68 (1.12)	2.62 (0.80)	2.17 (0.66)
890	6.76 (2.06)	3.85 (1.17)	2.75 (0.84)	2.27 (0.69)
960	7.04 (2.15)	4.01 (1.22)	2.86 (0.87)	2.38 (0.73)
1,000	7.20 (2.19)	4.10 (1.25)	2.94 (0.90)	2.43 (0.74)
1,700	9.61 (2.93)	5.54 (1.69)	4.01 (1.22)	3.35 (1.02)
1,800	9.91 (3.02)	5.73 (1.75)	4.15 (1.26)	3.47 (1.06)
2,000	10.70 (3.26)	6.09 (1.86)	4.43 (1.35)	3.71 (1.13)
2,300	11.54 (3.52)	6.63 (2.02)	4.60 (1.40)	4.07 (1.24)
2,700	12.61 (3.84)	7.30 (2.13)	5.11 (1.56)	4.53 (1.38)
3,000	13.44 (4.10)	7.81 (2.38)	5.43 (1.66)	-
3,400	14.44 (4.40)	8.52 (2.60)	-	-
4,000	15.81 (4.82)	9.42 (2.87)	-	-
5,000	17.77 (5.42)	10.84 (3.30)	-	-