

## JTDW-TP-xxxxxx-DF



????????(HIGH POWER WIDEBAND TRIPLEXER)

?: ????  
1-4 Weeks  
★ ★ ★ ★ ★

[????????](#)

??

Model Number	JTDW-TP-81821-DF			JTDW-TP-182126-DF			JTDW-TP-801821-DF		
	890-960	1710-2170	2500-2690	1710-1880	1920-2170	2490-2690	790-960	1710-1880	1920-2170
Insertion Loss (dB)	±0.3	±0.4	±0.4	±0.5	±0.5	±0.4	±0.2	±0.5	±0.5
Isolation (dB)	≥50	≥50	≥50	≥50	≥50	≥50	≥50	≥50	≥50
VSWR	≤1.3	≤1.3	≤1.3	≤1.3	≤1.3	≤1.3	≤1.3	≤1.3	≤1.3
Input Power (W)	200(average per port)			300(average per port)			300(average per port)		
Impedance (ohm)	50			50			50		
PIM3 (dBc @ 2*43dBm)	≤ -153 & ≤ -160								
Connector	N-female & DIN-female & 4.3-10-female								
Color	Gray-plated								
Application	Indoor & Outdoor IP67								
Temperature(°C)	-25~+60			-25~+60			-25~+60		
Mounting	Pole or Wall Mount			Pole or Wall Mount			Pole or Wall Mount		
Relative Humidity	5-95%			5-95%			5-95%		