

## Fiber Link-108



Fiber Link-108(Cable Access)



Fiber Optic Repeater 5GNR 4800MHz TDD

??: ????  
1-2 months  
★ ★ ★ ★ ★


[??????????](#)

??

- 2 ??????IP65????????????????
- 2 Tx/Rx????????????????????
- 2 ??????????????
- 2 ??WDM????????????
- 2 ??5G??TDD????????????5G????????????????
- 2 ??MU?????8?RU????????????MU?RU??????????
- 2 USB/RJ45????????????????????IP?NMS????????????????????????????????????
- 2 Aluminum-alloy casing with IP65 protection has high resistance to dust, water and corrosion.
- 2 Tx/Rx control and alarm messages can be transmitted via one fiber optic cable.
- 2 Stable and improved signal transmission quality.
- 2 Adopting WDM module to realize long-distance transmission.
- 2 Built-in 5G Dynamic TDD Sync Detection Module, automatic completion of 5G wireless network

cell search and wireless signaling processing.

- 2 One MU can support up to 8 RUs to maximize utilization of fiber optic cable, A star topology is supported between MU and RUs.
- 2 USB/RJ45 port provides a link to a notebook for local supervision or IP Based NMS (Network Management System) that can remotely supervise repeater's working status and download



operational parameters to the repeater via Ethernet.