

## TS080206xxA1



TS080206xxA1

DC-6000MHz UWB 2W Inline Attenuators

?: ????  
1-4 Weeks  
★ ★ ★ ★ ★

[?????????](#)

??

## UWB 2W Inline Attenuators

Tone Spread’s 2 Watt Inline Attenuators are designed to attenuate the power that is supplied by a source or input, up to 2 watts down, to the desired level as the power input for the next element in the network. These are fixed, in-line attenuators.

Tone Spread’s passive attenuator reduces the amount of power being delivered to the connected load by a single fixed amount.

Part Number:	Descriptions:	Product Image:
TS08020603A1	3dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	
TS08020605A1	5dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	
TS08020606A1	6dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	
TS08020610A1	10dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	
TS08020615A1	15dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	
TS08020620A1	20dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	
TS08020630A1	30dB Attenuator Low PIM DC-6000MHz 2W 4.3-10M-F n/s PIM IP65	