

TS-S37L-DW



TS-S37L-DW Brochure

LTE1800+2100 Outdoor Dual Band RF Repeater(85dB /37dBm)

?: ????
1-4 Weeks
★ ★ ★ ★

[????????](#)

??

?????

- Ø ??????????????
- Ø ?????????????????????
- Ø ?????????????????
- Ø ????????????
- Ø ?????????????????????
- Ø MGC ?????????????????
- Ø ?????????????????????????????????????
- Ø ???????????ALC/AGC????????????????????
- Ø ?????????????????
- Ø LCD????????????????????????????????????
- Ø ???????????

Key features

- Ø Two signal ports with full duplex design.
- Ø Linear power amplification to effectively suppress inter-modulation and spurious emission.
- Ø Stable and improved signal transmission quality.
- Ø Compact size with stable performance.
- Ø Auto Isolation check between service and donor antennas.
- Ø MGC available for both uplink and downlink.
- Ø Smart mode to auto-adjust gain according to the isolation and signal level received by donor site.
- Ø Smart Automatic Level Control (ALC/AGC) ensures output level stable and adjustable continuously.
- Ø Auto shut off function available for both uplink and downlink.
- Ø LCD real time display to show the instant power and gain for each link.
- Ø Low interference & Oscillation prevention.