

4800-4900MHz 兩埠全向吸頂天線

CE-M2-4849-2DBN



Tone Spread
Solutions for Wireless Signal

Communications Technology & Engineering Accessories

Rev.V1.0

電器規格 (Electrical Characteristics)

頻率範圍 (Frequency Range)	4800-4900MHz
電壓駐波比 (VSWR)	< 2.0
效率 (Efficiency)	≈ 65%
增益 (Peak Gain)	2dBi
阻抗 (Impedance)	50 Ohm
極化 (Polarization)	Linear
水準波瓣寬度 (Horizontal Beam Width)	360°
垂直波瓣寬度 (Vertical Beam Width)	65±10°
最大功率 (Max Power)	50W
不圓度	±1.5

機械規格 (Material & Mechanical)

接頭類型 (Connector Type)	N-K *2
天線尺寸 (Dimension)	Φ 86*40±1mm
重量 (Weight)	0.11Kg
天線外罩材料 (Radome material)	ABS (白色)

環境 (Environmental)

工作溫度 (Operation Temperature)	- 45°C ~ +85 °C
存放溫度 (Storage Temperature)	- 45°C ~ +85 °C
工作濕度 (Operation Humidity)	< 95%
抗風強度 (Rated Wind Velocity)	36.9m/s
防雷保護 (Lighting Protection)	直流接地

產品照片 (Photo)

