

TS7C00A/TS7B20A



UHF Fiber Optic Repeater



400-470 MHz UHF Fiber Optic Repeater

??: ????
On Order
★★★★★

[??????????](#)

??

UHF Fiber Optic Repeater is an active distributed antenna system designed to extend wireless communication coverage. It is primarily used to resolve **UHF (Ultra High Frequency, typically between 380-512 MHz) signal blind spots or weak reception issues** in large buildings, underground tunnels, mining areas, or regions far from the Base Transceiver Station (BTS). By utilizing fiber optic cables for long-distance, low-loss signal transmission, it is particularly suitable for public safety systems (such as TETRA, P25), enterprise private networks (DMR/PMR), and two-way radio signal extensions.

System Components & Working Principle

A UHF fiber optic repeater system typically adopts a two-layer architecture, consisting of the following two core units:

Master Unit / Donor Unit (MU):

I Installed near the Base Transceiver Station (BTS) or at a location capable of receiving a strong wireless signal.

I Captures the RF (Radio Frequency) signal from the base station via a direct coupler or a donor antenna.

I Converts the internal RF signal into an **optical signal** and transmits it over long distances through a single-mode fiber optic network.

Remote Unit / Coverage Unit (RU)

I Deployed in the target blind zones requiring signal coverage (e.g., inside tunnels, basements).

I Receives the optical signal from the fiber optic cable and **converts it back into an RF signal**.

I Amplifies the signal using an internal power amplifier and broadcasts it through indoor/outdoor coverage antennas to terminal devices (such as walkie-talkies or radios).

I Conversely, the uplink signal from terminal devices travels back along the reverse path to the base station.

